



BSP Size, Inches	Outside Diameter, mm
¼	10
⅜	13
½	21
¾	27
1	33
1¼	42
1½	48
2	60
2½	73
3	89

### 1. Bleed valves,

⅜" BSP chrome. £2.50.

⅜" also available in brass, £2.50

¼" BSP brass, £3.50

½" BSP brass, £4.50.



### 2. Steel blanking plugs. ½" and ¾" BSP shown. Right hand thread only. £3 each

**3 & 4. Gaskets.** 50P each. Available in white or black silicone. 1½" or 1¼" BSP. Also available in old fashioned fibre, 1½" BSP only. 1½" BSP is the correct size for all Castrads' radiators except 5 Column and King 768. For 5 Column and King 768 use 1¼" BSP. 1½" BSP also fits reclaimed 4 column radiators. Fibre gaskets require a very high compression to get a good seal. Silicone gaskets are much easier to work with.

**5. Nipples.** £2 each. Used to join one section of radiator to the next. Available in 1½" and 1¼" BSP. Use with the assembly tool (6).

**6. Assembly Tool.** £50 to buy outright or £80 to hire with £50 refundable upon return. Fits all Castrads radiators. Does *not* fit reclaimed radiators.

**7. Steel/brass reducing bushes.** £2 to £10 each depending on size. Right hand thread only.

**8, 9, 10. Cast iron reducing bushes and plugs.** £4 each. 1½" BSP male to ¾", ½", ⅜" or no hole; 1¼" BSP male to ½", ⅜" or no hole. Left or right hand male thread. Use with gasket, 50P, to make a seal around male thread